



Lenovo G40-30 Keyboard Replacement

Replacing the keyboard is a quick and easy...

Written By: Luke



INTRODUCTION

Replacing the keyboard is a quick and easy task. Removing the keyboard only took three tools: A JIS #1 screwdriver, plastic opening tool, and tweezers. Before you start make sure you remove the battery and unplug the device.

🔧 TOOLS:

[iFixit Opening Tool](#) (1)

[Tweezers](#) (1)

[JIS #1](#) (1)

Step 1 — Battery




- At the top of the laptop you will see two switches, like in image one and two.
- Pull the switches outwards with your thumb, towards the unlocked lock.

Step 2



- Once both switches are pulled, the battery should pop out.

Step 3



- Now you are ready to insert your new battery.

Step 4 — Keyboard




- Use a JIS #1 screwdriver to remove the two 7 mm screws.

Step 5



- Remove the back panel by sliding it away from the battery.

Step 6



- Use a JIS #1 screwdriver to remove the three 7 mm screws.

Step 7



- Wedge the plastic opening tool in-between the keyboard and the base of the laptop.
 - Continue using the plastic opening tool to pry around the edge until the keyboard is completely freed from the frame.
 - The keyboard should only be connected by a ribbon on the underside of the keyboard.
- ⓘ It is recommended that you slowly pull the keyboard out as you move around the edge. As in picture 2.
- ⚠ Be careful not to pull the keyboard too far away from the face as it will damage the data ribbon.

Step 8



- Use the [tweezers](#) to lift the black hinge on the ribbon connector.
- Then pull the ribbon from the connector and remove the keyboard from the laptop.

Step 9



- Now your keyboard is free to be replaced!

To reassemble your device, follow these instructions in reverse order.