



Motorola Moto G3 Screen Replacement

When the screen keeps on freezing or is unresponsive to touch, the screen needs to be replaced and this guide helps walk you through just how to do that.

Written By: Irkan Notta



INTRODUCTION

[Click here for an updated version of this guide.](#) The version you are viewing is retained for historical purposes.

In this guide, we will walk through how to replace the screen of the Motorola Moto G3.

TOOLS:

- [iFixit iOpener](#) (1)
 - [iFixit Opening Tools](#) (3)
 - [iOpener](#) (1)
 - [Tweezers](#) (1)
-

Step 1 — Prerequisite Guide



- Use the plastic opening tool to open the back cover as shown in the photo.

Step 2



- Heat an iOpener in the microwave for 30 seconds.
- Place the heated iOpener on all four edges of the screen for approximately 2 minutes.

Step 3



- Apply the plastic opening tool on the edge of the screen near the front camera.
- After creating enough space, allow the opening tool to be inserted on the side of the phone.
- Create another space on the other side of the screen.
- Leave the opening tool inserted.
- Carefully apply the larger plastic opening tool by sliding it through the longer edge of the screen.

Step 4



- A strip will be attached to the motherboard as shown.
- Using tweezers, carefully detach the strip from the motherboard.

To reassemble your device, follow these instructions in reverse order.