




Olympus E-Pl1 Sensor Lens Replacement

This guide uses the "Opening the Case", and "Internal Assembly" guides as prerequisites for replacing the sensor lens. These guides are included as steps 1-10. This guide will help the user to replace the sensor lens on the camera.

Written By: Jeffery Smith




INTRODUCTION

This guide is designed to teach an ifixit user to replace the sensor lens for an Olympus E-PL1 camera.

TOOLS:

- [Phillips #000 Screwdriver](#) (1)
 - [Spudger](#) (1)
 - [Tweezers](#) (1)
 - [Soldering Iron](#) (1)
-


Step 1 — Opening The Case



- Push the gray tab down, using a spudger if necessary, and the battery will come out.


⚠ Failure to remove the battery prior to disassembly can result in harm.

Step 2




- There are a total of six screws that must be removed using the the #000 Philips screwdriver.
- As per picture one: there is one 4.9 mm Philips head screw on the left side of the camera.
- As per picture two: on the bottom of the camera, there are three 3.4 mm Philips head screws; these are located on the darker area of the case.
- As per picture three: there are two 5.3 mm Philips head screws on the right side, one is beneath the USB cover.

Step 3




- Open the case by peeling off the back panel.
- ⚠ Pull the case apart gently so that the ribbon connector will not tear.

Step 4




- Disconnect the two ribbon cables as shown in picture one.
- ⚠ Avoid using metal pry tools, as shown in the photo, on internal electronic components, as it can cause a short and damage the device. Use an ESD-safe tool such as a standard nylon spudger.
- ℹ To disconnect a ribbon cable, use a spudger to lift the black tab then pull the ribbon out. This works the same for all ribbon cables.

Step 5




- The back panel has now been removed.

Step 6 — Sensor Assembly



- Using a spudger, remove the ribbon cables by pushing the black tab back and gently pulling the cable out.
- ⚠ Avoid using metal pry tools, as shown in the photo, on internal electronic components, as it can cause a short and damage the device. Use an ESD-safe tool such as a standard nylon spudger.
- Do this process for the two ribbon cables shown in the third photo.

Step 7




- Using the #000 Phillips screwdriver, remove the 4.3 mm screw as shown by the screwdriver and the 6.0 mm screw holding down the ribbon.

⚠ **These screws have washers on them, do not to lose them.**


- Using tweezers, gently lift the ribbon off the sticky pad.

Step 8





- Unlike previous connectors, this cable has a light grey clip holding it in place on opposite side of the connector in regards where the ribbon is inserted. Flip it up and then using your fingers, gently pull the top ribbon cable out.

Step 9



- Using a #000 Phillips screwdriver, remove the 6.0 mm screw on the bottom left hand corner. You can locate the screw on the picture as the green circle.

Step 10




- In the upper left hand corner, use the #000 Phillips screwdriver to remove the 6.0 mm screw.

✦ *Retain the copper washer held in by this screw.*

- Using tweezers gently lift the copper grounding strip.


⚠ **Do not tear the strip as you pull it off, it must stay attached to the main camera body.**

Step 11



- Remove the bracket in the lower right hand corner. In order to do so, you must remove two different screws.
- Using the #000 Phillips screwdriver, remove the 2.4 mm screw on the bottom.
- Using the #000 Phillips screwdriver, remove the 6.0 mm screw on the top and lift off the bracket.



Step 12



- Now you can lift out the sensor assembly. The following steps will explain how to lift it out.
- First, slightly lift the bottom half following the direction of the arrow.
- Second, lift the top left up side up. It may be a little stuck so you will have to wiggle it out.
- Finally, pull the entire assembly towards the bottom and away from the case.


⚠ There is a ribbon connector that is beneath the assembly. Be careful when lifting the assembly out. Do not yank it out very hard or you may damage the ribbon connector.

Step 13




- This is the sensor assembly with the photo showing the connected ribbon cable.
- ✦ *There are three washers held in by the 6.0 mm screws as shown in picture two. Be sure to replace them when reassembling.*

Step 14




- The sensor assembly has been removed.

Step 15 — Sensor Lens




- Remove the 3 screws surrounding the sensor lens with a #000 Phillips screwdriver.

Step 16



- Using a soldering iron and soldering wick desolder the two wires connecting the lens.
- ★ **take note of the colors of the wire as the new lens must be attached in the same manner.**
- Solder in the new lens. Be sure to match the wire color to the original wire placement.

Step 17



- Remove the sensor lens by pulling back as shown.

To reassemble your device, follow these instructions in reverse order.